

Performance Series



	MG90	MP70	RV55	RV50X	GX450
TECHNOLOGY SUPPORTED	LTE-A Pro, LTE-A, HSPA+	LTE-A Pro, LTE-A, HSPA+	LTE-A Pro, HSPA+ LTE-M/NB-IOT (Global)	LTE-A, HSPA+	LTE, HSPA+, EVDO, GSM
MAX CELLULAR SPEED (DL/UL Mbps)	LTE-A Pro: 600/150 LTE-A: 300/50	LTE-A Pro: 600/150 LTE-A: 300/50	LTE-A Pro: 600/150 LTE-M: 300kbps/375kbps LTE-NB: 27kbps/65kbps	LTE-A: 300/50	LTE: 100/50
APPROVED CARRIERS	Verizon, AT&T/FirstNet, Sprint, Southern Linc, Rogers, Telus, Bell	Verizon, AT&T/FirstNet, Sprint, Southern Linc, Rogers, Telus, Bell, Telstra	Verizon, AT&T/FirstNet	Verizon, AT&T, Sprint, Rogers, SaskTel, Telstra, Telus	Verizon, AT&T, Sprint, US Cellular, Rogers, Bell, Telus, SaskTel
NAVIGATION	48 Channel Dedicated GNSS with Inertial Dead Reckoning	48 Channel Dedicated GNSS with Inertial Dead Reckoning	30 Channel GPS/GLONASS	12 Channel GPS/GLONASS	12 Channel GPS/GLONASS
HOST INTERFACE	5 Ethernet (10/100/1000) 1 Serial (RS232) 2 USB 3.0 5 GPIO 1 Bluetooth	4 Ethernet (10/100/1000) 1 Serial (RS232) 1 USB 2.0 (micro) 5 GPIO 1 OBD-II/J1939 (Direct Vehicle CAN Interface)	1 Ethernet (10/100/1000) 2 Serial (RS232) with accessory cable 1 USB 2.0 (micro) 1 GPIO	1 Ethernet (10/100/1000) 1 Serial (RS232) 1 USB 2.0 (micro) 1 GPIO	1 Ethernet (10/100) 1 Serial (RS232) 1 USB 2.0 (micro) 1 GPIO
SIM SLOT (2FF)	4	2	2	2	1
WI-FI	Dual Radio 2.4/5GHz 802.11 b/g/n/ac 3x3 MIMO 4 SSIDs	2.4/5GHz (Optional) 802.11b/g/n/ac 3x3 MIMO 4 SSIDs	Dual Radio, 2.4/5GHz (Optional) 802.11 b/g/n/ac 1x1 SISO 1 SSID per radio	N/A	2.4GHz (Optional) 802.11b/g/n 1x1 SISO
WI-FI CLIENTS/ SECURITY	128 clients WPA2-Personal/Enterprise	128 clients WPA2-Personal/Enterprise	10 clients per radio WPA2 Personal/Enterprise	N/A	8 clients WPA2-PSK
SECURITY	FIPS 140-2 (compatible), Port filtering AAA (802.1x/RADIUS) MAC Address filtering	FIPS 140-2 (compatible), Port filtering, IP whitelist AAA (LDAP, RADIUS, TACACS+) MAC Address filtering Secure Firmware Update	FIPS 140-2 (compatible), Port filtering, IP whitelist AAA (LDAP,RADIUS, TACACS+) MAC Address filtering Secure Firmware Update	FIPS 140-2 (compatible), Port filtering, IP whitelist AAA (LDAP, RADIUS, TACACS+) MAC Address filtering Secure Firmware Update	FIPS 140-2 (compatible), Port filtering, IP whitelist AAA (LDAP, RADIUS, TACACS+) MAC Address filtering Secure Firmware Update
VPN	IPSec: IKEv1/IKEv2, Split/full tunnel, MOBIKE 10 concurrent tunnels Dead Peer Detection	IPSec: IKEv1/IKEv2, Split/full tunnel, MOBIKE, Open-VPN, GRE Tunnel, Split Tunnel, VPN failover 5 concurrent tunnels Dead Peer Detection	IPSec: IKEv1/IKEv2, Split/full tunnel, MOBIKE, Open-VPN, GRE Tunnel, Split Tunnel, VPN failover 5 concurrent tunnels Dead Peer Detection	IPSec: IKEv1/IKEv2, Split/full tunnel, MOBIKE, Open-VPN, GRE Tunnel, Split Tunnel, VPN failover 5 concurrent tunnels Dead Peer Detection	IPSec: IKEv1/IKEv2, Split/full tunnel, MOBIKE, Open-VPN, GRE Tunnel, Split Tunnel, VPN failover 5 concurrent tunnels Dead Peer Detection
INDUSTRY STANDARD	Environment	MIL-810G/IP64	MIL-810G/IP64	MIL-810G/IP64	MIL-810G/IP64
	Vehicle /Rail Usage	E-Mark, SAE J1455, ISO7637-2, EN50155	E-Mark, SAE J1455, ISO7637-2, EN50155	E-Mark, SAE J1455, ISO7637-2, EN50155	E-Mark, SAE J1455, ISO7637-2
	Industrial	N/A	Class 1 Div 2	Class 1 Div 2	Class 1 Div 2
AIRLINK MOBILITY MANAGER	Yes	Yes	Yes	Yes	Yes
AIRLINK MANAGEMENT SERVICE	No	Yes	Yes	Yes	Yes
CUSTOMER SUPPORT	AirLink Support	AirLink Complete	AirLink Complete	AirLink Complete	AirLink Complete
OPERATIONAL VOLTAGE	7-36VDC	7-36VDC	7-36VDC	7-36VDC	9-36VDC
OPERATING TEMPERATURE	-30°C to +70°C	-30°C to +70°C	-30°C to +70°C	-40°C to +70°C	-30°C to +70°C
ENCLOSURE	Die-cast aluminium	Die-cast aluminium	Die-cast aluminium	Die-cast aluminium	Die-cast aluminium
OPTIONAL UPGRADES	OBD-II/J1939/1708 (with Scanner Kit)	Wi-Fi OBD-II/J1939 Direct Vehicle Bus Cable	Dual Wi-Fi Dual Serial (Y cable)	N/A	Wi-Fi / Dual Serial / I/O Telemetry OBD-II (with Scanner Kit)
DIMENSIONS	272mm x 220mm x 60mm 10.71" x 8.66" x 2.36"	190mm x 105mm x 45mm 7.48" x 4.13" x 1.77"	119 mm x 85 mm x 33 mm 4.69" x 3.35" x 1.34"	119 mm x 85 mm x 34 mm 4.68" x 3.34" x 1.34"	142mm x 98mm x 41 mm 5.59" x 3.86" x 1.61"
WARRANTY	3 Years with 2 years extended option	3 Years with 2 years extended option	3 Years with 2 years extended option	3 Years with 2 years extended option	3 Years with 2 years extended option
MORE INFORMATION	sierrawireless.com/mg90	sierrawireless.com/mp70	sierrawireless.com/rv55	sierrawireless.com/rv50	sierrawireless.com/gx450

AirLink® Routers and Gateways

Essential Series



	LX60	LX40	ES450
TECHNOLOGY SUPPORTED	LTE, HSPA+ LTE-M/NB-IoT (Global)	LTE, HSPA+ LTE-M/NB-IoT (Global)	LTE, HSPA+, EVDO, GSM
MAX CELLULAR SPEEDS (DL/UL Mbps)	LTE: 150/50 LTE-M: 300kbps/375kbps NB-IoT: 27kbps/65kbps	LTE: 150/50 LTE-M: 300kbps/375kbps NB-IoT: 27kbps/65kbps	LTE: 100/50
APPROVED CARRIERS	Verizon, AT&T	Verizon, AT&T	Verizon, AT&T, Sprint, T-Mobile, US Cellular, Rogers, Bell, Telus
NAVIGATION	48 Channel Dedicated GNSS (Optional)	N/A	N/A
HOST INTERFACE	2 Ethernet (10/100/1000) 1 Serial (RS232/485) 1 USB 2.0 (micro) 5 GPIO	1 Ethernet (10/100/1000) 1 USB 2.0 (Micro) 1 GPIO PoE - Powered Device	1 Ethernet (10/100) 1 Serial (RS232) 1 USB 2.0 (micro) 1 GPIO
SIM SLOT (2FF)	1	1	1
WI-FI	2.4/5GHz (Optional) 802.11b/g/n/ac 1x1 SISO 1 SSID	2.4/5GHz (Optional) 802.11b/g/n/ac 1x1 SISO 1 SSID	N/A
WI-FI CLIENTS/ SECURITY	10 clients WPA2 Personal/Enterprise	10 clients WPA2 Personal/ Enterprise	N/A
SECURITY	FIPS 140-2 (compatible), Port filtering, IP whitelist AAA (LDAP, RADIUS, TACACS+) MAC Address filtering Secure Firmware Update	FIPS 140-2 (compatible), Port filtering, IP whitelist AAA (LDAP, RADIUS, TACACS+) MAC Address filtering Secure Firmware Update	Port filtering, IP whitelist AAA (LDAP, RADIUS, TACACS+) MAC Address filtering Secure Firmware Update
VPN	IPSec: IKEv1/IKEv2, Split/full tunnel, MOBIKE, OpenVPN, GRE Tunnel, Split Tunnel, VPN failover 5 concurrent tunnels Dead Peer Detection	IPSec: IKEv1/IKEv2, Split/full tunnel, MOBIKE, OpenVPN, GRE Tunnel, Split Tunnel, VPN failover 5 concurrent tunnels Dead Peer Detection	IPSec, OpenVPN, GRE Tunnel, Split Tunnel, VPN failover 5 concurrent tunnels Dead Peer Detection
INDUSTRY STANDARD	Environment	MIL-810G/IP21	MIL-810G/IP64
	Vehicle Usage	E-Mark, SAE J1455, ISO7637-2	E-Mark, SAE J1455, ISO7637-3
	Industrial	Class 1 Div 2	Class 1 Div 2
AIRLINK MOBILITY MANAGER	Yes	Yes	Yes
AIRLINK MANAGEMENT SERVICE	Yes	Yes	Yes
CUSTOMER SUPPORT	AirLink Complete	AirLink Complete	AirLink Complete
OPERATIONAL VOLTAGE	7-36VDC	7-36VDC, PoE - Powered Device	9-36VDC
OPERATING TEMPERATURE	-30°C to +65°C	-30°C to +65°C	-20°C to +60°C
ENCLOSURE	Polycarbonate	Polycarbonate	Die Cast Aluminum
OPTIONAL UPGRADES	Wi-Fi, GNSS	Wi-Fi	N/A
DIMENSIONS	146 mm x 100 mm x 42 mm 5.74" x 3.93" x 1.65"	103 mm x 79 mm x 25 mm 4.1" x 3.1" x 1.0"	142mm x 98mm x 41 mm 5.59" x 3.86" x 1.61"
WARRANTY	3 Years with 2 years extended option	3 Years with 2 years extended option	3 Years with 2 years extended option
MORE INFORMATION	sierrawireless.com/lx60	sierrawireless.com/lx40	sierrawireless.com/es450